200058
D7C 18 V 10 POK-IBSL
Inductive proximity sensor

- Closed, all-steel sleeve
- 3-times the standard operating distance
- Same operating distance to steel and aluminum
- Housing and sensing face made of stainless steel
- Insensitive to aggressive cleaning agents, environmental influences and hot filings
- Metal connector
- Integrated amplifier
- Short-circuit protection
- Starting pulse suppression
- LED





1) LED 2) Width over flats 24 mm BN: brown BU: blue WH: white

Function

Technical data (typ.)	+20°C, 24 V DC
Electrical features	
Service voltage	10 … 30 V DC
Internal power consumption	< 12 mA
Insulation voltage endurance	According to IEC 60947-5-2 (7.2.3.1)
Mechanical features	
Installation type	Flush
Thread	M18 x 1
Housing length	63.5 mm
Housing material	Stainless steel
Tightening torque	50 Nm
Certifications, approvals	
Protection class	III, operation on protective low voltage
Approvals	UL
General features	
Operating principle	inductive
Evaluation	digital
Design	Thread
Characteristics	extremely high operating distance, < 60 bar, Full-metal casing closed

200058
D7C 18 V 10 POK-IBSL
Inductive proximity sensor

Technical data (typ.)	+20°C, 24 V DC
Design	Solid metal housing
Product series	INW Full metal
Functional scope	
Scope of delivery	Sensor, 2 x M18 nuts
Output, input, interface	
Switching output	pnp, 200 mA, NC
Voltage drop (max.)	2 V
Detection range, measuring range, tolerance limits	
Switching distance (SN)	10 mm
Standardized measuring plate	30 x 30 x 1 mm
Switching hysteresis (max.)	15 % (5 % typ.)
Time behavior	
Switching frequency	200 Hz
Ambient conditions	
Ambient temperature during operation	-25 … +70 °C
Protection type	IP 68
Electrical connection	
Connection	Connector, M12, 4-pin, A-coded
Accessories	
Connection cable	VK …
More information / accessories	**https://www.di-soric.com/200058**

© di-soric . Right to change reserved