200309
DCC 12 M 10 PSLK
Inductive proximity sensor

- Highly flexible cable
- Integrated amplifier
- Short-circuit protection
- Starting pulse suppression
- LED





1) LED 2) Width over flats 17 mm BK: black BN: brown BU: blue

Function

Technical data (typ.)	+20°C, 24 V DC
Electrical features	
Service voltage	10 … 30 V DC
Internal power consumption	< 10 mA
Insulation voltage endurance	According to IEC 60947-5-2 (7.2.3.1)
Mechanical features	
Installation type	non-flush
Thread	M12 x 1
Housing length	50 mm
Housing material	Brass (chromium-plated)
Material of cable	PVC
Certifications, approvals	
Protection class	III, operation on protective low voltage
Approvals	UL
General features	
Operating principle	inductive
Evaluation	digital
Design	Thread
Characteristics	extremely high operating distance

© di-soric . Right to change reserved

200309
DCC 12 M 10 PSLK
Inductive proximity sensor

Technical data (typ.)	+20°C, 24 V DC
Product series	INE Industrial
Functional scope	
Scope of delivery	Sensor, 2 x M12 nuts
Output, input, interface	
Switching output	pnp, 200 mA, NO
Voltage drop (max.)	2 V (200 mA)
Detection range, measuring range, tolerance limits	
Switching distance (SN)	10 mm
Standardized measuring plate	30 x 30 x 1 mm
Switching hysteresis (max.)	3 … 15 %
Time behavior	
Switching frequency	400 Hz
Ambient conditions	
Ambient temperature during operation	-25 … +70 °C
Protection type	IP 67
Electrical connection	
Connection	Cable, 2.0 m (flying leads)

More information / accessories	https://www.di-soric.com/200309

© di-soric . Right to change reserved