





201710 TKHM-W-10/LP Connection cable

- LEDs for service voltage and switching status
- Drag chain compatible
- Sturdy metal union nut
- Durable PU coating
- Flexible lead design
- Good stripping properties
- High protection type
- Gold-plated plug-in contacts



1) Mounting free space from upper edge of plug connector
2) LED (2x) only with TKHM-W- ... / LP

BK: black

BN: brown

BU: blue

Function



Technical data (typ.)

Electrical features

Service voltage < 30 V DC

Mechanical features

Length 10,000 mm
Diameter Ø 4.5 mm (Diameter)
Thread M8 x 1
Material of cable Polyurethane, unshielded
Drag chain properties 70 mm (Min. bending radius)

Certifications, approvals

Protection class III, operation on protective low voltage

General features

Design Angled / open cable end
Characteristics Metal nut

Functional scope

Drag chain compatible Yes

Display, operation

LED Anzeige Yes

Ambient conditions

Ambient temperature during operation -5 ... +80 °C (Movable, Fixed)
Protection type IP 67



201710
TKHM-W-10/LP
Connection cable

Technical data (typ.)

Electrical connection

Connection

Socket, M8, 3-pin, A-coded

Cross-section

0.25 mm² (3 x)

More information / accessories

<https://www.di-soric.com/201710>