




201743 VL-TZSA-TZKA-3JBK-100X-S Cable connection

- Drag chain compatible
- Sturdy metal union nut
- Flexible lead design
- High protection type



Function



Technical data (typ.)

+20°C, 24 V DC

Electrical features

Service voltage	max. 50 V AC / max. 60 V DC
Operating current	max. 4 A / Contact

Mechanical features

Length	1,000 mm
Diameter	Ø 4.1 mm (Diameter)
Thread	M8 x 1
Material of cable	Polyurethane, Black, unshielded
Material	■ Die-cast zinc (Socket) ■ Die-cast zinc (Connector)
Drag chain properties	■ max. 10 Mio. (Bending cycles) ■ 10 x Ø (Min. bending radius) ■ 3 m/s (Max. moving speed) ■ ± 180 °/m (Max. torsion)
Tightening torque	0.4 Nm (recommended)

Certifications, approvals

Protection class	III, operation on protective low voltage
------------------	--

General features

Component	Cable connection
Design	Straight / straight
Characteristics	Metal nut

Functional scope

Drag chain compatible	Yes
-----------------------	-----

Ambient conditions

Temperature range	-25 ... +80 °C (Movable), -40 ... +80 °C (Fixed)
Protection type	IP 65 / IP 66K / IP 67

**201743****VL-TZSA-TZKA-3JBK-100X-S****Cable connection****Technical data (typ.)****+20°C, 24 V DC****Electrical connection**

Connection

Connector, M8, 3-pin, A-coded

Connection 2

Socket, M8, 3-pin, A-coded

Cross-section

0.25 x 0.25 mm (3 x)

More information / accessories**<https://www.di-soric.com/201743>**