





207950

OT 18 FKR 600 P3-B4

Retroreflective diffuse sensor

- Angled optics
- Universal mounting options
- Low installation depth
- Sensitivity is adjustable
- LED switching status display
- Plastic housing



- 1) Potentiometer
2) LED

- 3) Width over flats 24 mm
4) Lateral light emission

BK: black

BN: brown

BU: blue

WH: white

Function



Technical data (typ.)

+20°C, 24 V DC

Electrical features

Service voltage	10 ... 30 V DC
No-load current (max.)	30 mA

Mechanical features

Thread	M18 x 1
Housing length	67.5 mm
Housing material	Plastic (ABS)
Material	PMMA (Window)

Certifications, approvals

Protection class	III, operation on protective low voltage
------------------	--

General features

Operating principle	Retroreflective diffuse sensor
Evaluation	digital
Design	Thread, Angled optics

Output, input, interface

Switching output	pnp, 100 mA, NO/NC
------------------	--------------------



207950
OT 18 FKR 600 P3-B4
Retroreflective diffuse sensor

Technical data (typ.)

+20°C, 24 V DC

Optical data

Light source	LED
Color	Infrared
Wavelength	880 nm
Modulation	Clocked
Ambient light immunity	3 kLx Clocked light, 10 kLx Sunlight

Detection range, measuring range, tolerance limits

Range	600 mm
Standardized measuring plate	200 x 200 mm

Display, operation

Sensitivity adjustment	Potentiometer
------------------------	---------------

Time behavior

Switching frequency	1000 Hz
Response time	0.50 ms
Release time	0.50 ms

Ambient conditions

Ambient temperature during operation	-25 ... +55 °C
Protection type	IP 67

Electrical connection

Connection	Connector, M12, 4-pin
------------	-----------------------

More information / accessories

<https://www.di-soric.com/207950>