





207956 OR 18-1 FK 5700 P3 Retroreflective sensor

- Universal mounting options
- Low installation depth
- Sensitivity is adjustable
- LED switching status display
- Plastic housing



1) Potentiometer
2) LED

3) Width over flats 24 mm

BK: black

BN: brown

BU: blue

WH: white

Function



Technical data (typ.)

+20°C, 24 V DC

Electrical features

Service voltage	10 ... 30 V DC
No-load current (max.)	30 mA

Mechanical features

Thread	M18 x 1
Housing length	44.5 mm
Housing material	Plastic (ABS)
Material of cable	PVC
Material	PMMA (Window)

Certifications, approvals

Protection class	III, operation on protective low voltage
------------------	--

General features

Operating principle	Retroreflective sensor
Evaluation	digital
Design	Thread

Functional scope

Scope of delivery	Sensor
-------------------	--------



207956
OR 18-1 FK 5700 P3
Retroreflective sensor

Technical data (typ.)

+20°C, 24 V DC

Output, input, interface

Switching output	pnp, 100 mA, NO/NC
Voltage drop (max.)	2 V

Optical data

Light source	LED
Color	Red
Wavelength	660 nm
Modulation	Clocked
Ambient light immunity	3 kLx Clocked light, 10 kLx Sunlight

Detection range, measuring range, tolerance limits

Range	5000 mm
Range during operation with	■ 2000 mm (R55) ■ 4500 mm (R 84) ■ 5000 mm (R 100x100)
Referring reflector	100 x 100 mm, R 100 x 100

Display, operation

Sensitivity adjustment	Potentiometer
------------------------	---------------

Time behavior

Switching frequency	1000 Hz
Response time	0.50 ms
Release time	0.50 ms

Ambient conditions

Ambient temperature during operation	-25 ... +55 °C
Protection type	IP 67

Electrical connection

Connection	Cable, 2.0 m
------------	--------------

More information / accessories

<https://www.di-soric.com/207956>