214755
VL-TZSA-TWKA-4PBK-30X
Cable connection

- Sturdy metal union nut
- Flexible lead design
- High protection type



1) Cable length

Function

Technical data (typ.)	+20°C, 24 V DC
Electrical features	
Service voltage	max. 50 V AC / max. 60 V DC
Operating current	max. 4 A / Contact
Mechanical features	
Length	300 mm
Diameter	Ø 4.8 mm (Diameter)
Thread	M8 x 1
Material of cable	PVC, Black, unshielded
Material	■ Die-cast zinc (Socket) ■ Die-cast zinc (Connector)
Weight	20 g
Tightening torque	0.4 Nm (recommended)
Certifications, approvals	
Protection class	III, operation on protective low voltage
General features	
Design	Straight / angled
Characteristics	Metal nut
Ambient conditions	
Temperature range	-5 … +80 °C (Movable), -30 … +80 °C (Fixed)
Protection type	IP 65 / IP 66K / IP 67
Electrical connection	
Connection	Connector, M8, 4-pin, A-coded
Connection 2	Socket, M8, 4-pin, A-coded
Cross-section	0.25 x 0.25 mm (4 x)

More information / accessories	https://www.di-soric.com/214755

© di-soric . Right to change reserved

© di-soric . Right to change reserved