





214818

INE-M30/78T-N15NO-B4

Inductive proximity sensor

- Welding spark resistant due to PTFE coating
- Weld-proof
- Magnetic field test for DC/AC fields up to 150 mT



1) LED (4x)

BN: brown

BU: blue

WH: white

Function



Technical data (typ.)

+20°C, 24 V DC

Electrical features

Service voltage	10 ... 30 V DC
No-load current (max.)	10 mA
Inverse polarity protection	Yes
Short-circuit protection	Yes

Mechanical features

Installation type	non-flush
Thread	M30 x 1.5
Housing length	78 mm
Housing material	Brass (PTFE coated)
Material of sensor probe	PTFE

General features

Operating principle	inductive
Evaluation	digital
Design	Thread
Design	Weld-proof
Product series	INE Industrial



214818
INE-M30/78T-N15NO-B4
Inductive proximity sensor

Technical data (typ.)		+20°C, 24 V DC
Functional scope		
Scope of delivery	Sensor, 2 x M30 nuts	
Output, input, interface		
Switching output	npn, 200 mA, NC	
Voltage drop (max.)	1.5 V	
Detection range, measuring range, tolerance limits		
Switching distance (SN)	15 mm	
Switching hysteresis (max.)	15 %	
Display, operation		
LED Anzeige	Yes	
Time behavior		
Switching frequency	200 Hz	
Ambient conditions		
Ambient temperature during operation	-25 ... +70 °C	
Protection type	IP 67	
Electrical connection		
Connection	Connector, M12, 4-pin	
More information / accessories		https://www.di-soric.com/214818