214906
OH34-LRMS-TI-G3-T4
Retroreflective diffuse sensors with background suppression

- Compact stainless steel housing
- Protection class IP 69K
- ECOLAB approval
- Small detection angle
- Ideal background suppression
- Laser red light with small light spot
- DD mode, evaluates intensity and distance simultaneously
- Push-pull output with pnp or npn function
- Switch for light/dark switching
- IO-Link
- Sensing range and window function can be parameterized in mm





BK: black BN: brown BU: blue WH: white

Function

IO-Link

Technical data (typ.)	+20°C, 24 V DC
Electrical features	
Service voltage	10 … 30 V DC
No-load current (max.)	< 30 mA
Inverse polarity protection	Yes
Short-circuit protection	Yes
Mechanical features	
Housing dimensions	32 x 21 x 11 mm
Housing length	21 mm
Housing height	32 mm
Housing width	11 mm
Housing material	Stainless steel
Material	Plastic (Window / optics)
Weight	22 g
Certifications, approvals	
Protection class	III
Approvals	UL

214906
OH34-LRMS-TI-G3-T4
Retroreflective diffuse sensors with background suppression

Technical data (typ.)	+20°C, 24 V DC
General features	
Operating principle	Diffuse sensor with background suppression
Evaluation	digital
Design	Cuboid design
Default setting	Switching frequency (350 Hz (PRECISION))
Output, input, interface	
Switching output	Push-pull, 100 mA, NO/NC, switchable
Voltage drop (max.)	1 V
Interface	IO-Link (V1.1, COM2 38.4 kBd, Smart Sensor Profile)
Optical data	
Light source	Laser
Laser class	CLASS 1 LASER PRODUCT
Color	Red
Wavelength	650 nm
Background suppression	Yes
Light spot size	Ø 1 mm (at distance of 300 mm)
Detection range, measuring range, tolerance limits	
Range	20 … 100 mm
Standardized measuring plate	200 x 200 mm
Display, operation	
Sensitivity adjustment	Button, IO-Link
Display	LED green - Status, yellow - Switching output 1
Time behavior	
Switching frequency	350 Hz … 800 Hz (350 Hz (HIGH FUNCTIONAL RELIABILITY), 800 Hz (SPEED))
Ambient conditions	
Ambient temperature during operation	-25 … +60 °C
Protection type	IP 67 / IP 69K
Electrical connection	
Connection	Connector, M8, 4-pin
Accessories	
Connection cable	TK … /4

© di-soric . Right to change reserved

214906
OH34-LRMS-TI-G3-T4
Retroreflective diffuse sensors with background suppression

Background suppression - precise mode



1) Distance sensor / object (mm)
2) Minimum distance between object and background (mm)
3) Sensor
4) object
5) background
6) Typical behavior - object black (6%) / background white (90%)
7) Typisches Verhalten - Objekt blanc (90%) / Hintergrund blanc (90%)

Typical detection diagram (white 90%) - Precise mode (Factory setting)



1) Distance sensor / standard targe (mm)
2) Offset (mm)
3) Sensor
4) Standard targe

Typical detection diagram (white 90%) - Fast mode



1) Distance sensor / standard targe (mm)
2) Offset (mm)
3) Sensor
4) Standard targe

© di-soric . Right to change reserved

More information / accessories	**https://www.di-soric.com/214906**

© di-soric . Right to change reserved