





214934 AL-VZKA-12JBK-1500W-AS Connection cable

- Sturdy metal union nut
- Flexible lead design
- High protection type
- Robust PUR coating
- 12-pin
- Drag chain compatible
- Shielded



Function



Technical data (typ.)

Electrical features

Service voltage	max. 30 V AC/DC (with max. 1.5 A)
-----------------	-----------------------------------

Mechanical features

Length	15,000 mm
Diameter	Ø 6.5 mm (Diameter)
Thread	M12
Material of cable	Polyurethane, Black, shielded
Drag chain properties	■ > 10 Mio. (Bending cycles) ■ Fixed: 5 x Ø, Movable: 10 x Ø (Min. bending radius) ■ 3 m/s (Max. moving speed) ■ 180 °/m (Max. torsion)

General features

Component	Connection cable
Design	Straight / open cable end
Characteristics	Metal nut
To be used for	CS 6x Vision Sensors, ID Reader - ID 6x0

Functional scope

Drag chain compatible	Yes
-----------------------	-----

Display, operation

LED Anzeige	No
-------------	----

Ambient conditions

Ambient temperature during operation	-25 ... +85 °C
Protection type	IP 65 / IP 66K / IP 67

**214934****AL-VZKA-12JBK-1500W-AS****Connection cable****Technical data (typ.)****Electrical connection**

Connection

Socket, M12, 12-pin, A-coded, 12 x 0.14 mm²**More information / accessories**<https://www.di-soric.com/214934>