215725
ID520-BM325-EP5/300PRO
ID-520 Fixed-mounted ID Readers

- Locate code, read code, count codes, code grading
- Upgrade option: Read plain text
- Ultra compact & very high-performing
- Internal LED lighting in white
- Flexible and productive Software nVision-i
- Parameter changes via linked Profinet inputs during execution
- Simple & intuitive parameterization
- Integrated lens with 25 mm focal length
- Flexible working distances



1) Green – operation, Red – signal digital input
2) Green – Data Link, Red – Ethernet Signal

12-pol A-codiert

1	NC	7	Power (21-28V)
2	Digital IN1	8	GND
3	Digital Out2	9	NC
4	NC	10	Trigger (Digital IN0)
5	READY (Digital Out3)	11	Digital OUT0
6	NC	12	Digital OUT1

8-pol X-codiert

1	LAN A+	5	LAN D+
2	LAN A-	6	LAN D-
3	LAN B+	7	LAN C-
4	LAN B-	8	LAN C+

Function

PROFINET EtherNet/IP™

Technical data (typ.)	+20°C, 24 V DC
Electrical features	
Service voltage	21 … 28 V DC
No-load current (max.)	1000 mA (24 V DC)
Inverse polarity protection	No
Short-circuit protection	No
Insulation voltage endurance	500 V
Mechanical features	
Housing material	Aluminum (Black, powder-coated)
Material	PMMA (Window / optics)
Lens connection	S-mount
Weight	125 g
General features	
Model	ID520
Design	Cuboid design
Sensor type	SONY IMX900

© di-soric . Right to change reserved

215725
ID520-BM325-EP5/300PRO
ID-520 Fixed-mounted ID Readers

Technical data (typ.)	+20°C, 24 V DC
Functional scope	
Code type - 1D-Codes (barcodes)	Code 2 of 5, Codabar, Code 128, Code 39, Databar, UPC / EAN, Pharmacode
Code type - 2D-Codes	Aztec Code, Data Matrix, Dotcode, QR
Code type - Stacked codes	PDF 417
Internal lights	White
Output, input, interface	
Switching output	Open Emitter, 50 mA, 3 (programmable), 1 (Ready)
Voltage drop (max.)	2 V
Interface	Digital Input/Output
Protocols	TCP/IP, FTP/SFTP, Profinet, EtherNet/IP
Optical data	
Color	White (internal)
Focal length	25 mm
Detection range, measuring range, tolerance limits	
Resolution	1440 x 1080 Pixel (1.6 MP)
Ambient conditions	
Protection type	IP 50
Electrical connection	
Connection	Connector, 0.2 m, M12, 12-pin, A-coded
Connection 2	Socket, M12, 8-pin (X-coded)
Cable	Connection cables max. 25 m

More information / accessories	https://www.di-soric.com/215725

© di-soric . Right to change reserved . 31.07.2026